

LED Panel Series



VT-2929

HIGHLIGHTS :

WATTS



29

EQ. WATTS



200

LUMINOUS



2800

BEAM ANGLE



110

| | |
|-----------------------|-----------------------|
| Item No | : VT-2929 |
| SKU Code | : 4940 |
| Watts | : 29 |
| EQ Watts | : 200 |
| Voltage | : AC:220-240V,50/60Hz |
| Lumen(lm) | : 2800 |
| Color Temperature | : 3000K |
| Beam Angle | : 110 |
| Commercial type | : ROUND |
| PF | : >0.9 |
| LED Chip Type | : SMD |
| CRI | : >80 |
| Energy rating label | : A+ |
| Certification | : EMC,LVD,ROHS |
| Body type | : DIE CAST ALUMINUM |
| Dimmable | : No |
| Life Time | : 20,000 Hours |
| Operation Temperature | : -20~50'C |
| EAN code | : 3800157606561 |
| Unit size | : 200mm x 27mm |
| Cutting size | : 185mm |
| Packing details | : 40 |
| Unit cbm | : 0.001471 |

PRODUCT FEATURES

- Compare with incandescent, it can save over 80% electric cost
- Contemporary & Elegant Design
- Higher Light Transmission Rate
- No flickering, No U.V Radiation
- No Lead or Mercury content hence Environment friendly
- Suitable for office and genral lighting (Conference Room, Showroom, lobby, cabin, kitchen etc.)
- High quality power driver
- Instant light 100% O s
- Temp -20 to + 45'C

[CLICK HERE FOR OTHER RELATED CERTIFICATES](#)