

Product Specification Sheet

200W VT-9217 200W SMD HIGHBAY WITH MEANWELL DRIVER COLORCODE:4000K 120'D 5YRS WARRANTY Equivalent Lumens **Beam Angle** Dimensions 1600W 26000 120 400x187mm Day White YEARS 80 SKU:5593 WARRANTY

Technical Information

1600 IP Rating: IP65 200 Dinmable: Yes 26000 Warranty (Years): 5 120 PF: >0.9 Black CRI: >70 Aluminium Die Cast Operation Temperature: -25 to +50°c		
200 Dimmable: Yes 26000 Varranty (Years): 5 120 PF: >0.9 Black CRI: >70 Aluminum Die Cast Operation Temperature: -25 to +50°c	Instant Start:	0-100% in lt1s
26000 Warranty (Years): 5 120 PF: >0.9 Black CRI: >70 Aluminium Die Cast Operation Temperature: -25 to +50°c	EQ-WATTS:	1600
120 PF: >0.9 Black CRI: >70 Aluminium Die Cast Operation Temperature: -25 to +50°c	Watts:	200
Black CRI: >70 Aluminium Die Cast Operation Temperature: -25 to +50°c	Lumens:	26000
Aluminium Die Cast Operation Temperature: -25 to +50°c	Beam Angle:	120
	Unit Color:	Black
A++ Input Power: AC:100-240V,50/60Hz	Body Type:	Aluminium Die Cast
	Energy Rating:	A++
20,000 Hours Sensor Compatibility: Yes	Long life:	20,000 Hours

Features



Aluminium Diffuser with multiple Beam Angle's to choose from 45 D / 90 D / 120 D

- Shatter Proof Perspex Lens
- High Thermal Conductivity, Low Luminous Decay, Pure Colours & No Heavy Shade

Applications - Industrial Usage, Warehouse & Super Markets, Workshop's, Factories, Warehouse's and many more

Note: (24H)

Suitable & Recommended for maximum daily use of 10-12 hours

Packaging

Unit Details	
Length(Box)mm	445
Width(Box)mm	440
Height(Box)mm	185
Unit CBM	0.041625
Master Box Packaging	
Master Box Qty (Pcs Per Carton)	2
Qty Per Pallet	32

