

Product Specification Sheet



50W

VT-4955 50W SMD SLIM FLOODLIGHT COLORCODE:4500k WHITE BODY-WHITE WIRE

Equivalent 250W

Lumens **4250**

Beam Angle 100

Dimensions 237x194x38mm

Day White SKU:5826









Technical Information

Instant Start:	0-100% in lt1s
EQ-WATTS:	250
Watts:	50
Lumens:	4250
Beam Angle:	100
Unit Color:	White
Body Type:	Die Cast Aluminium
Energy Rating:	A+
Long life:	20 000 Hours

 LED Chip Type:
 SMD2835

 IP Rating:
 IP65

 Dimmable:
 No

 Warranty (Years):
 2

 PF:
 >0.9

 CRI:
 >70

 Operation Temperature:
 -25 to +50°c

 Input Power:
 AC:220-240V,50/60Hz

 Sensor Compatibility:
 Yes



Features

- ✓ Perfect replacement of Metal Hallide Floodlight, High Pressure Sodium Floodlight & Halogen Floodlight
 - Available in different color options of White , Day White, Warm White and RGB
- Fascia glass sealed with SILICONE RUBBER ensuring superior waterproof /airtight performance
- Premium Quality Aluminium Alloy body
- High Power LED chip
 - Corrosion Resistant
- Built in driver no external power supply required
 - Excellent coverage for area and façade lighting
- Available from 10W up to 1000W
 - Application Building Façade, Sports Facilities, Industrial, Commercial Bill Boards & Hoardings, Parking Lots etc



Packaging

Unit Details

Qty Per Pallet

Unit CBM 0.004032

Master Box Packaging

Master Box Qty (Pcs Per Carton) 10

400

Listing Details

 EAN Code
 3800157615006

 Commodity Code
 9405403990



