

Product Specification Sheet



Technical Information

Instant Start:	0-100% in It1s	Body Type:	PC
Watts:	2	Long life:	20,000 Hours
Lumens:	160	LED Chip Type:	SMD
Battery Charging Current:	30mA	IP Rating:	IP20
Battery Discharging Current:	160mA	Dimmable:	No
No. Of Led:	16	Warranty (Years):	2
Battery Type:	Ni-Cd 4.8V,600mAh	Operation Temperature:	-20 to +45°c
Charging Time:	24 Hours	Input Power:	AC:220-240V,50/60Hz
Emergency Operation Time:	>3 Hours		

Features

- Efficient thermal management technology.
- High performance Ni-Cd batteries made for Longevity & low maintenance.
- LEDs mounted on print circuit board.
- Low energy consumption only 2.0 watts at 120V.
- Thermoplastic PC housing, Rectangular type plastic with different signs.
- Single or double face configuration.
- Reliable Emergency backup of 3 hours.
- Universal (wall, side or ceiling) mounting.
- LED indicator light and push button test switch.

Packaging

Unit Details		Listing Details	
Length(Box)mm	50	EAN Code	3800157623155
Width(Box)mm	340	Commodity Code	9405403990
Height(Box)mm	250		
Unit CBM	0.00436		
Master Box Packaging			
Inner Box Qty	10		
Master Box Qty (Pcs Per Carton)	10		
Qty Per Pallet	240		

